PS-137

PS-137 Interactive Kiosk







FEATURES

- Versatile self-service kiosk
- Sleek & space-saving stand-alone design
- 21.5" full HD touch display (500 nits)
- Built-in 3-inch printer
- Customizable with many peripheral options
- Latest, high-performance Intel or Rockchip CPU
- Available for Android, Linux, and Windows

PS-137

Specifications



Item	PS-137		
Size	21.5"		
Aspect Ratio	16:09		
Resolution	1920 x 1080		
Brightness	500 nits		
Touch	PCAP Touch		
CPU	**Alder Lake** Intel® Core™ i3-1215U Intel® Core™ i5-1245U, vPro Intel® Core™ i7-1265U, vPro	**Elkhart Lake** Intel® Celeron® J6412	**Rockchip** RK3399
Memory	DDR4 4GB, 8GB, 16GB, 32GB		LDDR4 4GB
Storage	M.2 PCIe SSD: 128GB / 256GB / 512GB /1TB		eMMC 32GB + 1x micro SD card slot
I/O Ports	3 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2, COM3)		2 x serial ports, RS-232 (RJ45) 0V/5V/12V selected in setting (COM1, COM2)
	1 x Intel LAN (IEEE 802.3 10/100/1000 Mbps)		1 x LAN (IEEE 802.3 10/100/1000 Mbps)
	1 x RJ11 port support for two cash drawers with 24V/12V jumper setting		
	1 x DC +12V out		
	4 x USB 3.2 + 2 x USB 2.0	3 x USB 3.2 + 3 x USB 2.0	1 x USB 3.0 (OTG) + 5 x USB 2.0
	1 x DC +12V input		
	1 x Audio (1 x line-out)		
	1 x HDMI		
	1 x Type-C (Data transfer + Display)		1 x Micro SD card
Printer	Compatible with RP-700 / RP-710 / Epson TM-M30II		
Barcode Scanner	2D Scanner (MP150) / optional cover for CF4680 & FM3281		
Speaker	1 x Speaker (3W)		
Peripheral Options	2D Barcode reader, MSR, payment terminal bracket, RFID/NFC reader, ADA/EAA keypad, LED status light (multi-color)		
Wireless Options	Wi-Fi 6E (Intel AX210), IEEE 802.11 a/b/g/n/acR2/ax (2.4 GHz, 5 GHz, 6 GHz)		IEEE 802.11a/b/g/n/ac (2.4 GHz, 5 GHz)
	BT 5.3		BT 4.2 (supports BLE)
Operating System	Windows 11 IoT Enterprise LTSC 24H2 (64 bit)		Android 12
	Windows 10 IoT Enterprise LTSC 21H2 (64bit)		
	Linux Ubuntu 22.04		
TPM & vPro	Intel vPro (i5/i7 CPU only)	S/W TPM 2.0 (BIOS)	N/A
	S/W TPM 2.0 (BIOS)		
Power Adaptor	AC-In 100~240V / DC-Out 12V, 120W	AC-In 100~240V / AC-Out 12V, 90W	AC-In 100~240V / DC-Out 12V, 90W
Spill & Dust Resistant	Front panel IP65, entire unit IP54 certifed		
Reliability	System operating temperature: 0°C ~ 40°C		
	System humidity: 15% ~ 80%		
	Storage temperature: -20°C ~ 60°C		
Dimensions (W x H x D)	PS-137 (Landscape): 524 x 1480 x 400 mm		
	PS-137 (Portrait): 350 x 1576 x 400 mm		
Weight (Stand only)	25kg		

*Specification is subject to change without prior notice

Contact Now

Europe	+49 40 450 635-0	info@partner-tech.eu
United Kingdom	+44 1928 579 707	sales-uk@partner-tech.eu
Spain	+34 913 120632	comercial@partner-tech.eu
Slovenia	+386 1 566 25 20	prodaja@partner-tech.eu
Poland	+48 22 115 93 82	officepoland@partner-tech.eu
France		ptf-contact@partner-tech.eu
South Africa	+27 87 094 0355	PTSAInfo@partner-tech.eu