RP-110

RP-110 Desktop POS Printer



FEATURES

- Simple and sleek design
- High performance - 250mm/sec
- Wheel-type paper jam control
- Triple Interface connectivity (project based BT/ WiFi version)
- Front exit printing with wall mount capability
- Easy maintenance

RP-110

Specifications

	RP-110
Color	black
Print speed	up to 250mm/s
Paper type	Thermal receipt paper/black mark supported
Paper roll	Media width max. 80mm (3.14"), maximum outer diameter Φ83mm (3.2")
Paper roll core	12.5mm ± 0.5mm
Paper thickness	0.06-0.08mm
Print width	72±0.5mm
Paper path	Paper out up or front
Print density	576 points per row or 512 points per row
Dot Pitch / Resolution	0.125mm x 0.125mm, 203 dpi
Characters per line (CPL)	Font A (12x24) - 48 columns / 42 columns Font B (9x17) - 64 columns / 56 columns
Line space	3.75mm (adjustable by command)
Interface type	Standard: USB(B Type), Serial(RS- 232C(9pin)), Ethernet Option (project based): Bluetooth Smart Ready(Bluetooth5.0+BLE) or WiFi(802.11 a/b/g/n)
Character size	ANK character, Font A: 1.5mm×3.0mm (12×24 points) Font B: 1.1mm×2.1mm (9×17 points) Simplified/complex font: 3.0mm×3.0mm (24×24 points)
Figure	Monochrome BMP and other image files can be downloaded to FLASH
Barcode Type	1D: EAN-8, EAN-13, Code 39, Code 93, Code 128, ITF, UPC-A, UPC-E, Codabar, QR Code, PDF41
Emulation	ESC/POS Command compatible
Driver	Windows Driver(XP ~, Server2003 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver Android SDK, iOS SDK, Windows SDK
Extended character list	PC437(Std.Europe), (Katakana), PC850(Multilingual), PC860(Portugal), PC863(Canadian), PC865(Nordic), (West Europe), (Greek), (Hebrew), (East Europe), (Iran), (WPC1252), PC866(Cyrillic#2), PC852(Latin2), (PC858) , (IranII), (Latvian), (Arabic), (PT1511251)

RP-110

Specifications

	RP-110
Reliability MCBF / TPH Life	80 million lines / 150 km
Cutter Type	Guillotine
Cutter Life	1,500,000 cuts
Cutter method	partial/full cut
Sensor	paper end / cover open / black mark
Input buffer/ NV Flash	128Kbytes / 256Kbytes
Power adapter voltage input - output	AC 100-240V/50~60Hz - DC 24V/2.5A
Cash-box/drawer control	DC 24V/1A
Working environment	Temperature: 0°C~45°C; humidity: 10%~80%
Storage environment	Temperature: -10°C~60°C; humidity: 10%~90%
Dimensions (WxHxD)	136 x 132 x 174 mm
Weight	1.04kg

Contact Now

Europe	+49 40 450 635-0	info@partner-tech.eu
United Kingdom	+44 1928 579 707	sales-uk@partner-tech.eu
Spain	+34 913 120632	comercial@partner-tech.eu
Slovenia	+386 1 566 25 20	prodaja@partner-tech.eu
Poland	+48 22 115 93 82	officepoland@partner-tech.eu
France		ptf-contact@partner-tech.eu
South Africa	+27 87 094 0355	PTSAInfo@partner-tech.eu