RP-330L

RP-330L Thermal Printer



FEATURES

- 8MB Flash Logo RAM
- Printing Speed - 200 mm/sec
- 80mm paper width
- Supports full & partial cut method
- Wall mounting

RP-330L

Specifications

	RP-330L
Color	black (white project based)
Print speed	up to 200mm/s
Paper type	Thermal receipt paper/black mark supported
Paper roll / core	Media width max. 80mm (3.14“) / 12.5mm ± 0.5mm
Paper thickness	0.06-0.08mm
Print width	72 mm max.
Paper path	Paper out up or front
Dot Pitch / Reso-lution	0.141mm x 0.141mm, 180 dpi
Interface type	Standard: USB(B Type), Cash Drawer Option: Serial, Parallel, Ethernet
Driver	Windows Driver(XP, 7, 8.1, 10), Linux Driver, OPOS Driver (Windows 32/64 bit)
Reliability MCBF / MTBF / TPH Life	60 million lines / 360,000 hours / 160 km
Cutter Type / Life / Method	Guillotine / 1,500,000 cuts / partial&full cut
Sensor	paper end / cover open / paper near end / option: black mark
Input buffer/ NV Flash	128Kbytes / 256Kbytes
Power adapter voltage input - output	AC 100-240V/50~60Hz - DC 24V/1.75A
Working environment	Temperature: 0°C~45°C; humidity: 10%~80%
Storage environment	Temperature: -10°C~60°C; humidity: 10%~90%
Dimensions (WxHxD)	152 x 198 x 151 mm
Weight	1.7 kg

Contact Now

Europe	+49 40 450 635-0	info@partner-tech.eu
United Kingdom	+44 1928 579 707	sales-uk@partner-tech.eu
Spain	+34 913 120632	comercial@partner-tech.eu
Slovenia	+386 1 566 25 20	prodaja@partner-tech.eu
Poland	+48 22 115 93 82	officepoland@partner-tech.eu
France		ptf-contact@partner-tech.eu
South Africa	+27 87 094 0355	PTSAInfo@partner-tech.eu