RP-710

RP-710 Thermal Printer



FEATURES

- Cubic Type housing
- Ideal for Kiosk, SCO or under desk applications
- Supports IAP online upgrade, voice Broadcast, replaying, queuing function
- Optional: Bluetooth Smart Ready (BT 5.0 + BLE) or Wi-Fi or BT, Wi-Fi Combo

RP-710

Specifications

	RP-710
Color	black (white project based)
Print speed	up to 250mm/s
Paper type	Thermal receipt paper/black mark supported
Paper roll	58mm, 80mm, 82.5m maximum outer diameter Φ83mm (3.2“)
Paper roll core	12.5mm ± 0.5mm
Paper thickness	0.05-0.08mm
Print width	80mm
Dot Pitch / Resolution	0.125mm x 0.125mm, 203 dpi
Characters per line (CPL)	Font A (12x24) - 53 / 48 / 35 columns Font B (9x17) - 71 / 64 / 46 columns
Line space	3.75mm (adjustable by command)
Interface type	Standard: USB(B Type), Serial(RS- 232C(9pin)), Ethernet Option (project based): Bluetooth Smart Ready(Bluetooth5.0+BLE) and/or WiFi(802.11 a/b/g/n)
Character size	ANK character, Font A: 1.5mm×3.0mm (12×24 points) Font B: 1.1mm×2.1mm (9×17 points)
Figure	Monochrome BMP and other image files can be downloaded to FLASH
Barcode Type	1D: EAN-8, EAN-13, Code 39, Code 93, Code 128, ITF, UPC-A, UPC-E, Codabar, QR Code, PDF41
Emulation	ESC/POS Command compatible
Driver	Windows Driver(XP ~, Server2003 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver Android SDK, iOS SDK, Windows SDK
Extended character list	PC437(Std.Europe), (Katakana), PC850(Multilingual), PC860(Portugal), PC863(Canadian), PC865(Nordic), (West Europe), (Greek), (Hebrew), (East Europe), (Iran), (WPC1252), PC866(Cyrillic#2), PC852(Latin2), (PC858) , (IranII), (Latvian), (Arabic), (PT1511251)

RP-710

Specifications

	RP-710
Reliability MCBF / TPH Life	80 million lines / 150 km
Cutter Type	Guillotine
Cutter Life	2,000,000 cuts
Cutter method	partial/full cut
Sensor	paper end / cover open / black mark
Input buffer/ NV Flash	128Kbytes / 256Kbytes
Power adapter voltage input - output	AC 100-240V/50~60Hz - DC 24V/2.5A
Cash-box/drawer control	DC 24V/1A
Working environment	Temperature: 0°C~45°C; humidity: 10%~80%
Storage environment	Temperature: -10°C~60°C; humidity: 10%~90%
Dimensions (WxHxD)	125 x125 x 131.5 mm
Weight	0.9 kg

Contact Now

Europe	+49 40 450 635-0	info@partner-tech.eu
United Kingdom	+44 1928 579 707	sales-uk@partner-tech.eu
Spain	+34 913 120632	comercial@partner-tech.eu
Slovenia	+386 1 566 25 20	prodaja@partner-tech.eu
Poland	+48 22 115 93 82	officepoland@partner-tech.eu
France		ptf-contact@partner-tech.eu
South Africa	+27 87 094 0355	PTSAInfo@partner-tech.eu