Stan 27

Stan 27 Kiosk



Stan 27

Specifications

	Stan 27
Color	Satin white, RAL 9016. Any other RAL colour range on request
Material	Structure made of 2-4 mm steel sheet with a 10 mm thick base. High resistance industrial powder paint with a thickness of 35 microns
Closure system	Safety locking system with 135º front opening
Fan System	Forced ventilation system, 3xAirFlow 21-37CFM/Axial AC
CPU	Themis Argo: Processor at customer request (Intel® Celeron® J6412, Intel® i3-"i3-1115G4 e Intel® i5-1135G7) Tinker Board PC for Android - Rockchip RK3399
Memory	Argo version from 8 GB to 32 Gb (depending on the processor model) Android: Dual-CH LPDDR4 4GB
Storage	Argo 256 GB SATA III SSD Version (Other Sizes, On Demand) Version Android: 16GB eMMC + Micro SD(TF) card slot (push/pull)
Operating System	Windows 10 / Windows 11 / Android 12
Max. Resolution	1.920 x 1.080 (16:9)
Size	27"
Brightness	300 cd/m2
Contrast Ratio	3000:1
Viewing Angle	H:178° / V:178°
Frame Rate	60Hz
Backlight	LED
Supported Colors	16.7M Colours
Touch	10-point Projected Capacitive (PCT)
Scanner	1D-2D - USB Interfaces. 2D: PDF417, Data Matrix, QR Code, IP65, Contactless 1D: EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Databar (RSSExpand, RSS-Limited, RSS-14), Code 39, Code 11, MSI-Plessey
AC Power	100V-240V,50-60Hz
Dimensions	1800 L x 500 W x 165 H
Configurations	Single / Double / Wall Mount
Weight	60 kg

Stan 27

Specifications

	Stan 27
Impression method	Thermal Line Printing
Point density	203dpi x 203dpi
Print direction	Unidirectional with friction feed
Print width	72mm (2.83"), 576 dot positions (203dpi) 80mm (3.15"), 640 dot positions (203dpi)
Characters per line	Font A : 48 CPL (12x24) Font B : 64 CPL (9x17)
Print speed	220mm/seg max. (1/6inch feed)
Bracket (Option)	Bracket for payment terminal (on request)
Wifi (Option)	Dual band 2.4G/5GHz
Camera (Option)	HD Pro C930 Webcam - Max. Resolution: 1080p/30 fps -720p/30 fps. Automatic focus
Other options and peripherals	On request
VESA Mounting	VESA Wall Adapter
Microphone	On request

Contact Now

Europe	+49 40 450 635-0	info@partner-tech.eu
United Kingdom	+44 1928 579 707	sales-uk@partner-tech.eu
Spain	+34 913 120632	comercial@partner-tech.eu
Slovenia	+386 1 566 25 20	prodaja@partner-tech.eu
Poland	+48 22 115 93 82	officepoland@partner-tech.eu
France		ptf-contact@partner-tech.eu
South Africa	+27 87 094 0355	PTSAInfo@partner-tech.eu