
Self-Checkout


Starling











FEATURES

- 21.5” or 15.6” PCAP touch display
- AI-powered Camera for item identification, surveillance
- AI-powered Camera and age verification
- Security scale for weight verification (different sizes)
- Scanner and Thermal Printer
- EAA-Pad® for legal accessibility requirements (option)
- Electronic Article Surveillance (EAS)
- LED tri-light pole
- Bagging area options with different sizes (Medium, Large, XLarge)

Starling

For an optimized workflow



Increase Sales Capacity

Quick & Convenient

Intelligent Fraud Prevention

Starling

Specifications

Item	Starling	
Size	21.5”	15.6”
Aspect Ratio	16:9	
Resolution	1920 x 1080	1366 x 768 (option 1920 x 1080)
Brightness	300 nits	220 nits (option 400 nits)
Touch	PCAP touch	
CPU	Intel® Core™ i3-1215U (Alder Lake)	
	Intel® Core™ i5-1245U, vPro (Alder Lake)	
	Intel® Core™ i7-1265U, vPro (Alder Lake)	
Memory	DDR4 8GB, 16GB, 32GB	
Storage	M.2 PCIe SSD: 128G, 256G, 512G, 1TB	
I/O Interface	1 x RJ45 Ethernet (Host)	
	1 x RJ45 Ethernet (option: EMV Terminal)	
	2 x USB 2.0 (option)	
	1 x Power switch button	
Speaker	1 x Speaker 3W	
Printer	RP-710, Options: on request	
Barcode Scanner	Zebra, Datalogic	
Optional Peripheral	LED tri-light pole (Several options)	
	AI-powered camera module (item identification, surveillance, and age verification)	
	Security Scale module	
	Electronic Article Surveillance (EAS)	
	EMV Terminal Bracket	
	EAA-Pad® : Assistive, audio enabled keypad offering menu navigation	
Wi-Fi/BT(option)	Wi-Fi 6E Intel AX210	
	IEEE 802.11 a/b/g/n/acR2/axR2, BT 5.3	
Operation System	1. Windows 11 IoT LTSC 24H2 (64bit)	
	2. Linux (Ubuntu 22.04)	
SW (option)	SW TPM 2.0	
	Intel vPro (i5 /i7 only)	
Reliability	System Operating Temperature: 5~40°C / 32~104°F	
	System Humidity: 15% ~ 80%	
	Storage Temperature: -20~60°C / -4~140°F	
Dimensions (W x H x D)	With medium bagging area option: 1130 x 1775 - 2090** x 652 mm; 44.5 x 70 - 82** x 26 in With large bagging are option: 1435 x 1775 - 2090** x 652 mm; 56.5 x 70 - 82** x 26 in	
Certificates	CE, FCC	

*Specification is subject to change without prior notice
**Different height, depending on screen size and tri-light

Contact Now

Europe	**+49 40 450 635-0**	**info@partner-tech.eu**
United Kingdom	**+44 1928 579 707**	**sales-uk@partner-tech.eu**
Spain	**+34 913 120632**	**comercial@partner-tech.eu**
Slovenia	**+386 1 566 25 20**	**prodaja@partner-tech.eu**
Poland	**+48221159382**	**officepoland@partner-tech.eu**
France		**ptf-contact@partner-tech.eu**
South Africa	**+27 87 094 0355**	**ptsaInfo@partner-tech.eu**