THEMIS

TI-1010(A)

TI-1010 Mobile Solution



Partner Tech Europe

www.partner-tech.eu

TI-1010(A)

THEMIS

Specifications

	TI-1010	TI-1010A
Max Resolution	1280 x 800	
Size	10.1“	
Brightness	280 nits	
Contrast	600:1	
Response Time	10ms	
Viewing Angle	Right 75° Left 75° / Upper 75° Lower 75°	
Technology	LCD with LED backlight	
Touch	10-point PCAP touch	
CPU (fanless)	Intel® Celeron® J6412 (Elkhart Lake) 2,00 GHz up to 2,60 GHz, Quad-core	Rockchip RK3288 Quad-core Cortex-A17 up to 1.8 GHz
RAM	1 x 4GB DDR4, 2400 MHz SO-DIMM	2GB DDR3
Storage	1 x 120GB mSATA SSD 128GB M.2 NVME SSD	16GB eMMC Flash
OS	Windows 10 / 11 Enterprise LTSC or SAC	Android 8.1 (support Google Play Services)
DC in	1 x DC 12V input power-jack	1 x DC 12V input power-jack
LAN	1 x RJ45	1 x RJ45
USB	2 x USB 2.0	2 x USB 2.0
TF card	-	1 x
Reset Button	via SIM tool (not included	via SIM tool (not included)
Power On	via SIM tool	via SIM tool

TI-1010(A)

THEMIS

Specifications

	TI-1010	TI-1010A
Color	black	
VESA Mounting	75 x 75	
Material	Plastic with aluminum back housing with top flat panel glass	
Speaker	1x 2W	1x 3W
Power	AC-In 100~240V / DC-Out 12V/5A	AC-In 100~240V / DC-Out 12V/2A
Power over Ethernet	supports PoE+ (802.3at)	
Dimensions	275.46 mm (W) x 234.96 mm (H) x 68,03 mm (D)	
Weight	1.84 kg	
Operation Temperature	0°C ~ 50°C	
Storage Temperature	-20°C ~ 60°C	
2D scanner	supports all common 1D/2D barcodes	
NFC/RFID reader	supports LF and HF (125 kHz, 134.2 kHz and 13.56 MHz), supports all major transponders and ISO standards like ISO14443A/B (T=CL), ISO15693, ISO18092 / ECMA-340 (NFC)	

Contact Now

Europe	+49 40 450 635-0	info@partner-tech.eu
United Kingdom	+44 1928 579 707	sales-uk@partner-tech.eu
Spain	+34 913 120632	comercial@partner-tech.eu
Slovenia	+386 1 566 25 20	prodaja@partner-tech.eu
Poland	+48 22 115 93 82	officepoland@partner-tech.eu
France		ptf-contact@partner-tech.eu
South Africa	+27 87 094 0355	