Till.One

Till.One

Smart Compact POS











FEATURES

- All-in-One POS
- Intelligent cablemanagment
- Space-saving
- Printer RP-710 integrated
- POS Joy J-14 integrated
- Scalable with many peripheral options

Till.One

Specifications

		Till.One
Joy J14-1E	Display Size	14“
	Aspect Ratio	16:9
	Resolution	1366 x 768
	Brightness	220 nits
	Touch	PCAP
	CPU	Intel® Celeron® J6412 (Elkhart Lake)
	Memory	DDR4: 4GB - 32GB
	Storage	M.2 PCIe SSD: 128GB - 512GB
	I/O Interface	2 x Serial Ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2)
		1 x LAN (IEEE 802.3 10/100/1000 Mbps)
		1 x RJ11 (2 Cash Drawers with 24V / 12V jumper setting)
		1 x DC +12V out / 1 x DC +12V input
		2 x USB 3.0 + 4 x USB 2.0
		1 x Audio (1 x line-out)
		1 x HDMI
		1 x USB-C (data transfer only)
	Speaker	1x 3W
	Peripheral Options	MSR, EMV Reader, Fingerprint reader, RFID/ NFC, i-Button, VFD, USB 2nd display, HDMI 2nd displa 2D Barcode Scanner, Camera, IO-Extension-Box EX-300, Cash Drawer
	Wireless Option	Wi-Fi 6E Intel AX210 IEEE 802.11 a/b/g/n/acR2/axR2, BT 5.3
	Certification	IP65
	Operating System	Windows 10/11 IoT Enterprise LTSC 24H2 (64bit)
		Linux Ubuntu 22.04
	Power Adaptor	AC-In 100~240V / DC-Out 12V, 65W
Printer RP-710	Print speed	up to 250mm/s
	Paper type	Thermal receipt paper/black mark supported
	Paper roll	58mm, 80mm, 82.5m maximum outer diameter Φ83mm (3.2“)
	Paper thickness	0.05-0.08mm

Till.One

Specifications

Printer RP-710	Dot Pitch / Resolution	0.125mm x 0.125mm, 203 dpi
	Interface type	USB(B Type), Serial(RS- 232C(9pin)), Ethernet
	Barcode Type	1D: EAN-8, EAN-13, Code 39, Code 93, Code 128, ITF, UPC-A, UPC-E, Codabar, QR Code, PDF41
	Cutter Type	Guillotine
	Sensor	paper end / cover open / black mark
Till.One Mounting Solution	VESA	75 x 75
	Cable Cover	RAL 9005, ABS Plastic
	Adjustable	Seamlessly adjustable up to 135°
	Color	RAL 7021
	Material	2 mm cold-rolled steel
	Dimensions	Stand only: 130 x 340 x 130 mm
	Weight	Stand only: 1.62 kg
Dimensions (WxHxD)		340 x 370 x 150 mm
Weight		4.90 kg

Contact Now

Europe	+49 40 450 635-0	info@partner-tech.eu
United Kingdom	+44 1928 579 707	sales-uk@partner-tech.eu
Spain	+34 913 120632	comercial@partner-tech.eu
Slovenia	+386 1 566 25 20	prodaja@partner-tech.eu
Poland	+48 22 115 93 82	officepoland@partner-tech.eu
France		ptf-contact@partner-tech.eu
South Africa	+27 87 094 0355	PTSAInfo@partner-tech.eu