THEMIS

TS-1000

TS-1000 Scanner Solution



Partner Tech Europe

www.partner-tech.eu

TS-1000

THEMIS

Specifications

	TS-1000	
Image Size	1280 x 1024 pixels	
Reading Indicator	Beeper, LED	
Scanning Angle	± 60°, ± 54°, 360° (Skew, Pitch, Roll)	
Depth of Field	4 mil Code39 (9 chars) : 35 mm - 70 mm 5 mil Code39 (3 chars): 25 mm - 80 mm 10 mil Code39 (3 chars): 0 mm - 120 mm 13 mil UPC (6 chars) : 0 mm - 140 mm 15 mil Code39 (1 char) : 0 mm - 145 mm 20 mil Code39 (1 char): 0 mm - 145 mm 6.7 mil PDF417 (20 chars): 20 mm - 95 mm 10 mil QR (20 chars) : 10 mm - 100 mm 10 mil DM (20 chars) : 10 mm - 100 mm 20 mil QR (20 chars) : 0 mm - 150 mm	
Barcode Types	**1D** UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128 (GS1-128), ISBT 128, Code 93, Code 11 (USD-8) MSI/Plessey, UK/Plessey, China Post, China Finance, GS1 DataBar (formerly RSS) variants	**2D** PDF417, MicroPDF417, QR Code, MicroQR Code, DataMatrix, Han Xin Code, Aztec Code, GS1Composite
Humidity	5% ~ 95%	

TS-1000

THEMIS

Specifications

	TS-1000
Color	black
Certification	CE, LVD, IP52
Input Voltage	DC 5 +/- 0.25 V
Amperage	Working: 410mA, (Max: 700mA)
I/O Interfaces	RS-232, USB Keyboard, USB virtual COM
Cable	2m straight, RJ45 connector, field replaceable
Weight	482 g (without stand, without cable) 755 g (with stand, without cable)
Operat. Temperature	0°C ~ 50°C
Storage Temperature	-40°C ~ 70°C
Dimensions (WxHxD)	152.8 x 81.6 x 145.1 mm (without stand) 152.8 x 112 x 186.6 mm (with stand)

Contact Now

Europe	+49 40 450 635-0	info@partner-tech.eu
United Kingdom	+44 1928 579 707	sales-uk@partner-tech.eu
Spain	+34 913 120632	comercial@partner-tech.eu
Slovenia	+386 1 566 25 20	prodaja@partner-tech.eu
Poland	+48 22 115 93 82	officepoland@partner-tech.eu
France		ptf-contact@partner-tech.eu
South Africa	+27 87 094 0355	PTSAInfo@partner-tech.eu