THEMIS

TS-160

TS-160 Scanner Solution



Partner Tech Europe

www.partner-tech.eu

TS-160

THEMIS

Specifications

	TS-160
Image Size	1280 x 800 pixels
Reading Indicator	Beeper, LED, Vibrator
Scanning Angle	± 60°, ± 65°, ± 42° (Skew, Pitch, Roll)
Depth of Field	3 mil Code39 (3 chars): 20 mm - 70 mm 5 mil Code39 (3 chars): 0 mm - 120 mm 10 mil Code39 (3 chars): 0 mm - 280 mm 13 mil UPC-E (6 chars): 0 mm - 350 mm 20 mil Code39 (3 chars): 25 mm - 480 mm 30 mil Code39 (2 chars): 15 mm - 650 mm
Barcode Types	**1D** UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39,Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128, ISBT 128, Code 93, Code 11 (USD-8), MSI/Plessey, UK/Plessey, China Post, China Finance, GS1 DataBar (formerly RSS) variants
Humidity	5% ~ 95%
Decoding Rate	200 times per second
Drop Resistance	1.5 m
Radio Transmission	430.0 431.9 MHz , 433.3 434.7 MHz with adaptive frequency hopping
Working Range	Up to 100m
Certification	CE, LVD, IP51

TS-160

THEMIS

Specifications

	TS-160
Input Voltage	DC 5 +/- 0.25 V
Amperage	Working: 150mA, Standby 4mA
Weight	207 g
Operat. Temperature	0°C ~ 50°C
Storage Temperature	-40°C ~ 60°C
Dimensions (WxHxD)	90 x 70 x 180 mm
	TS-160 Handheld
Battery	Rechargeable Lithium-ion battery 1400mAh
Charge Time	4 hours
Working Time	Up to 21 hours
Standby Time	Up to 120 hours
Color	black, grey
	TS-160 Cradle
Drop Resistance	1.2 m
I/O Interfaces	RS-232, USB, PS/2
Dimensions (WxHxD)	118 x 89.5 x 74 mm
Weight	140 g

Contact Now

Europe	+49 40 450 635-0	info@partner-tech.eu
United Kingdom	+44 1928 579 707	sales-uk@partner-tech.eu
Spain	+34 913 120632	comercial@partner-tech.eu
Slovenia	+386 1 566 25 20	prodaja@partner-tech.eu
Poland	+48 22 115 93 82	officepoland@partner-tech.eu
France		ptf-contact@partner-tech.eu
South Africa	+27 87 094 0355	PTSAInfo@partner-tech.eu