THEMIS

TS-260

TS-260 Scanner Solution



Partner Tech Europe

www.partner-tech.eu

TS-260

THEMIS

Specifications

	TS-260		
Image Size	1280 x 800 pixels		
Reading Indicator	Beeper, LED, Vibrator		
Scanning Angle	± 75°, ± 75°, ± 360° (Skew, Pitch, Roll)		
Depth of Field		**HD**	**SR**
	3 mil Code3 (3 chars)	10 mm - 61 mm	/
	4 mil Code128 (9 chars)	5 mm - 88 mm	55 mm - 106 mm
	5 mil Code39 (3 chars)	0 mm - 108 mm	43 mm - 141 mm
	10 mil Code39 (3 chars)	0 mm - 108 mm	0 mm - 310 mm
	13 mil UPC (6 chars)	0 mm - 108 mm	0 mm - 335 mm
	20 mil Code39 (1 char)	10 mm - 253 mm	8 mm - 480 mm
	5 mil QR (40 chars)	7 mm - 65 mm	/
	6.7 mil PD417 (20 chars)	0 mm - 105 mm	37 mm - 145 mm
	10 mil QR (20 chars)	0 mm - 134 mm	0 mm - 168 mm
	20 mil QR (20 chars)	0 mm - 215 mm	0 mm - 345 mm
Barcode Types	all major 1D, GS1 DataBar, 2D		
Humidity	5% ~ 95%		
Scan Rate	60 frames/sec.		
Drop Resistance	1.5 m		
Radio Transmission	430.0 431.9 MHz , 433.3 434.7 MHz with adaptive frequency hopping		
Working Range	Up to 100m		
Certification	CE, LVD, IP51		

TS-260

THEMIS

Specifications

	TS-260
Input Voltage	DC 5 +/- 0.25 V
Amperage	Working: 350mA, Standby 20mA
Weight	210 g
Operat. Temperature	0°C ~ 50°C
Storage Temperature	-40°C ~ 60°C
Dimensions (WxHxD)	90 x 70 x 180 mm
	TS-260 Handheld
Battery	Rechargeable Lithium-ion battery 1400mAh
Charge Time	4 hours
Working Time	Up to 46 hours
Standby Time	Up to 100 hours
Color	black, grey
	TS-260 Cradle
Drop Resistance	1.2 m
I/O Interfaces	RS-232, USB, PS/2
Dimensions (WxHxD)	118 x 89.5 x 74 mm
Weight	140 g

Contact Now

Europe	+49 40 450 635-0	info@partner-tech.eu
United Kingdom	+44 1928 579 707	sales-uk@partner-tech.eu
Spain	+34 913 120632	comercial@partner-tech.eu
Slovenia	+386 1 566 25 20	prodaja@partner-tech.eu
Poland	+48 22 115 93 82	officepoland@partner-tech.eu
France		ptf-contact@partner-tech.eu
South Africa	+27 87 094 0355	PTSAInfo@partner-tech.eu