THEMIS

TS-500

TS-500 Scanner Solution



Partner Tech Europe

www.partner-tech.eu

TS-500

THEMIS

Specifications

	TS-500
Image Size	1280 x 800 pixels
Reading Indicator	Beeper, LED
Scanning Angle	horizontal: 64°, vertical 44° ± 50°, ± 60°, ± 360° (Skew, Pitch, Roll)
Depth of Field	4 mil Code 39: 15 - 55mm 3 mil UPC: 0 - 180mm 20 mil Code 39: 0 - 280mm 6.7 mil PDF 417: 15 - 70mm 10 mil QR: 10 - 40mm 20 mil QR: 0 - 140mm
Barcode Types	all major 1D, GS1 DataBar, 2D
Humidity	5% ~ 95%
Scan Rate	60 frames/sec.
Drop Resistance	1.5 m
Color	gray
Certification	CE, LVD
Options	Options USB, PS/2, RS-232 (interface selectable)

TS-500

THEMIS

Specifications

	TS-500
Input Voltage	DC 5 +/- 0.25 V
Amperage	Working: 350mA, Standby 135mA
I/O Interfaces	RS-232, USB HID/virtual COM, PS/2
Cable	2m straight, RJ45 connector, field replaceable
Weight	299 g (without cable)
Operat. Temperature	0°C ~ 50°C
Storage Temperature	-40°C ~ 70°C
Dimensions (WxHxD)	95 x 157 x 93 mm

Contact Now

Europe	+49 40 450 635-0	info@partner-tech.eu
United Kingdom	+44 1928 579 707	sales-uk@partner-tech.eu
Spain	+34 913 120632	comercial@partner-tech.eu
Slovenia	+386 1 566 25 20	prodaja@partner-tech.eu
Poland	+48 22 115 93 82	officepoland@partner-tech.eu
France		ptf-contact@partner-tech.eu
South Africa	+27 87 094 0355	PTSAInfo@partner-tech.eu