

Smart Mobile Terminal

# SUNMI L2Ks

Define a new classic for indoor applications and beyond.



## Better Protection Ratings

To withstand everyday usage, L2Ks is 1.8m drop resistant, IP68 rated and has passed 3000 0.5m tumble tests.

## ATL Large-capacity Battery, Safe And Durable

Equipped with a ATL battery cell, L2Ks features 800 charge cycles. The removable 5000mAh large-capacity battery can stand for up to 2 shifts. A new auxiliary battery helps eliminating downtime when changing the main battery.

## Professional Scan Engine

High speed — 10 scans/sec; long reach — up to one meter read distance; accurate — read just the barcode the laser aimer positioned; reliable — quickly read hard-to-read barcodes including scratched, stained, crinkled barcodes or DPM barcodes, etc.



## SUNMI L2Ks Tech Specs

<b>Model Approved</b> T8A10	<b>OS</b> SUNMI OS (*based on Android 11)	<b>CPU</b> Octa-core processor	<b>Memory</b> 4GB RAM+32GB ROM 2GB RAM+16GB ROM (Not supported for GMS Version)	<b>Display</b> 4"HD, 800x480 Capacitive IPS
<b>Camera</b> No GMS Version: Rear: 8MP AF GMS Version: Rear: 13MP AF Front: 5MP FF Rear camera for 1D / 2D barcode scanning	<b>NFC (optional)</b> Supports TypeA&B card, Mifare card, Felica card; ISO/IEC 14443 and ISO15693 compliant	<b>Speaker</b> 2* 1W	<b>PSAM Card Slot</b> 1*PSAM (optional)	<b>SIM Card Slot</b> 1* NANO SIM+1* SIM+ 1* MicroSD (TF)
<b>Sensors</b> Light sensor, proximity sensor, gravity sensor, gyroscope (optional), hall sensor (optional), E-compass (optional)	<b>Communication</b> 4G/3G/2G	<b>Wi-Fi</b> 2.4GHz/5GHz IEEE 802.11 ac/a/b/g/n/d/e/h/i/j/k/r/v/w	<b>Bluetooth</b> Bluetooth 5.0 BLE	<b>GPS</b> AGPS GPS/Glonass/Beidou/Galileo
<b>Buttons</b> 1* Function button 2* Left and right scan buttons 23* Physical buttons	<b>Microphones</b> 2* MIC	<b>Ports</b> 1*Type-C, support OTG 2*pogo pin at the bottom for charging 8* pogo pin on the back for accessories	<b>Battery</b> Removable polymer lithium battery, 3.8V/5000mAh Non-removable small battery 60mAh (optional)	
<b>vSIM</b> Only support China mainland	<b>Dimensions (L*W*H)</b> 160×64.5×14.4mm	<b>Total Weight</b> 243.5g	<b>Protection</b> IP68 1.8m drop spec	<b>Environment</b> Operating temperature: -20°C~55°C Storage temperature: -40°C~70°C
<b>Power Adapter</b> Type-C 5V/2A, 9V/2A	<b>Scanner</b> Professional scan engine (*Zebra & Honeywell are optional)	<b>Accessories (optional)</b> Trigger handle Charging base Four-slot battery charger Hand strap Screen tempered glass		